



PRODUCT SPECIFICATIONS

DREAMGUARD PROTEX3

DESCRIPTION

Liquid laminate for vinyl media and non water sensitive inks

CONSTRUCTION

Water based

UV inhibitors to protect against yellowing and cracking

AVAILABILITY

Three finishes: Satin, Matte and Gloss

1 pint sample, 1 gallon jug, 5 gallon bucket, 55 gallon drum

PURPOSE

To protect textured vinyl wallcoverings from scratches, abrasion and stains

To help extend the original appearance of printed wallcoverings

Designed to be applied without the need for laminating machines

APPLICATION

May be applied with paint roller or liquid laminating machinery

Milky white on application, dries clear in 1-2 hours

Use indoors, apply in temperatures between 55-85 degrees

Follow DreamGuard Application Instructions

COVERAGE

800 to 1200 sqft./gal.

ENVIRONMENTAL

Non-hazardous formulation, water based, MSDS available

Soap and water clean-up

Safe to ship, no VOC's

Safe for food contact when dry under FDA Regulations:

Code of Federal Regulations, Title 21, Food and Drugs

Part 175, Subpart A, Section 175.105

Part 175, Subpart A, Section 175.300

Part 176, Subpart B, Sections 176.170 & 176.180

FLAMMABILITY

DreamGuard Protex3 is non-flammable in both a wet and dried state and will not support flame

Test method used: UL94 HB (horizontal burn test)

COMMENTS

Keep from freezing.