

# Terralon™, Terralon Regatta™ and Terralon Smooth™ Technical Sheet 100117



<b>Product Name:</b>	<b>DreamScape Terralon, Terralon Regatta, Terralon Smooth</b>
<b>Description:</b>	PVC Free Eco-friendly digitally printable wallcovering , 54", 31% post consumer recycled content, for Latex, UV curable, Solvent + Eco Solvent inkjet printers
<b>Construction:</b>	100% Terralon™ (Proprietary Polyester/Natural Fiber Technology)
<b>Weight:</b>	14oz PLY / 435.2 G/PLM 9.3oz PSY / 315.3 G/PSM
<b>Thickness:</b>	22 mil.
<b>Availability:</b>	Roll sizes: 54" x 25 yds, 54"x 50 yds, 54"x 100 yds Trial Rolls (27"x15')
<b>Packaging:</b>	3" core, wound print side out, wrapped in black back, Shipped in heavy duty reusable cardboard tube
<b>Application:</b>	Standard commercial wallcovering pastes/primers and techniques. For indoor use in environmentally controlled spaces.
<b>Physicals:</b>	A lightweight alternative to vinyl that meets Type II physicals
<b>Print Ink(s):</b>	For printers using Solvent, Eco-Solvent, UV Curable and Latex inks
<b>Environmental:</b>	PVC & POA (Olefin) Free, No Plasticizers, No Phthalates, No Formaldehyde, No Chlorine, No Halogen, No Heavy Metals, including: Cadmium, Mercury, Lead, or Zinc, and No Ozone Depleting Chemicals. Minimum of 31% post-consumer recycled content Breathable* - very high permeability rating of 66 Perms based on ASTM E96 dry cup method Made with 100% water based adhesive systems No harmful off gassing Low Voc emitting
<b>Air Quality:</b>	Meets California Section IAQ 1350– Third party certified by Berkeley Analytical Associates
<b>Fire Testing:</b>	Class "A" Fire Rated – tested in accordance with ASTM-E84 Tunnel Test NFPA-101 (passed)
<b>LEEDS eligibility:</b>	Terralon™ can contribute towards the earning of up to 7 LEED credits.  Note: All Leed credits are based on the total construction of a building. Terralon offers up to a 50% advantage over competitive products for achieving MR Credit 4.1 and MR Credit 4.2 because of its higher percentage of post consumer recycled products.  MR Credit 4.1 Recycled content 10% MR Credit 4.2 Recycled content 20%  Conditionally- MR Credit 2.1 Contribution to project recycling program MR Credit 2.2 Contribution to project recycling program MR Credit 5.1 Manufactured local to the new construction EQ Credit 4.1 When mounted with use of low emitting adhesives EQ Credit 4.6 Contribution to low VOC emitting wall construction
<b>Warranty:</b>	5 Year Warranty against manufacturing defects. Additional information regarding warranty is available on our website at: <a href="http://www.dreamscapewalls.com/">http://www.dreamscapewalls.com/</a>
<b>Comments:</b>	**Permeable surface allows transfer of moisture to minimize possibility of mold and mildew growth. Nolar is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation, and/or accumulation at wall cavities and wall surfaces, especially in warm, humid climates. Dry cup tests performed by VARTEST Company.